



Explosion Proof Peristaltic Pump

Model No.: EXP600-1/EasyPump

Flow Rate: 3.18-3100mL/min



Product Features

- JDiven by explosion-proof motor, the power is strong.
- Stepless speed regulation, reversible inversion.
- IP rate: IP55, Explosion-proof grade:ExdIIBT4 Gb
- Suitable for inflammable and explosive industrial sites.

Pump Head



YZ35(PPS)

| Drive | Speed(rpm) | Pump Head | Tube Size | Flow Rate (mL/min) |
|-------------------|------------|-----------|--------------------------------------|--------------------|
| EXP600-1/EasyPump | 600 | EasyPump | 13#, 14#, 19#, 16#, 25#, 17#, 18# | 3.18-2580 |
| | | | 15#, 24#, 35#, 36# | 108-3100 |

Technical Specifications

| | |
|-------------------------|---|
| Speed range | Manual control: 180-600 rpm; Frequency converter control: 60-600rpm |
| Speed control | Manual stepless speed regulation/Inverter speed regulation |
| Voltage | 3 phase 380V(standard)/3 phase 220V(optional) |
| Condition temperature | 0-40°C |
| Relative humidity | <80% |
| Explosion-proof grade | ExdIIBT4 Gb, ExdIICT4 |
| IP rate | IP55 |
| Drive weight | 30kg |
| Drive dimension(L xWxH) | 424 x230x330(mm) |



■ Dimension Drawing(Unit:mm)

